



JIS B2220 -1995, JIS B2210-1984

単位: mm

呼び径		ボルト穴			ハブ部側内径の詳細			ガスケット面側			重量(kg)		
		中心径 C	数	径	S ₁	m	α°	内径の詳細			PL形	SO形	BL形
inch	mm	C			S ₁	m	α°	S ₂	n	l			
3/8	10	65	4	15	27	4	-	27	4.0	-	0.6	0.6	0.6
1/2	15	70	4	15	31	4	-	31	4.0	-	0.7	0.7	0.7
3/4	20	75	4	15	37	4	-	37	4.0	-	0.8	0.8	0.9
1	25	90	4	19	44	4	-	44	4.5	-	1.3	1.3	1.5
1 1/4	32	100	4	19	52	4	-	53	5.0	-	1.6	1.6	1.8
1 1/2	40	105	4	19	58	4	-	59	5.5	-	1.7	1.7	2.0
2	50	120	8	19	70	4	-	72	6.5	-	1.9	1.9	2.4
2 1/2	65	140	8	19	94	6	20°	85	6.0	6	2.6	2.6	3.4
3	80	160	8	23	107	6	20°	-	-	6	3.8	3.9	4.9
3 1/2	90	170	8	23	120	6	20°	-	-	6	4.4	4.6	6.0
4	100	185	8	23	132	6	20°	-	-	6	4.9	5.1	6.9
5	125	225	8	25	160	7	30°	-	-	6	7.8	8.3	11.0
6	150	260	12	25	186	8	30°	-	-	6	10.1	10.6	14.9
8	200	305	12	25	237	9	30°	-	-	6	12.6	13.3	21.4
10	250	380	12	27	290	10	30°	-	-	6	21.9	23.4	37.2
12	300	430	16	27	345	11	30°	-	-	6	25.8	27.7	48.8
14	350	480	16	33	384	12	35°	-	-	6	36.2	39.2	68.0
16	400	540	16	33	437	13	35°	-	-	7	51.7	54.2	99.4
18	450	605	20	33	490	15	35°	-	-	7	66.1	71.7	129.1
20	500	660	20	33	544	16	35°	-	-	7	77.4	86.2	158.4
22	550	720	20	39	595	16	35°	-	-	7	92.2	105.0	194.0
24	600	770	24	39	646	18	35°	-	-	7	101.1	119.0	226.9
26	650	850	24	48	-	-	-	-	-	-	147.6	-	311.6
28	700	900	24	48	-	-	-	-	-	-	168.0	-	370.9
30	750	970	24	56	-	-	-	-	-	-	212.7	-	460.1
32	800	1030	24	56	-	-	-	-	-	-	248.5	-	546.5
34	850	1090	24	56	-	-	-	-	-	-	280.5	-	626.2
36	900	1140	28	56	-	-	-	-	-	-	296.9	-	694.9

(1) 下記フランジの基本寸法は規定しているが、内径と形状の規定はない。(※下記の内径寸法は参考値とする。)